



# Paperband

For Reel Turn-up Systems

## General

Paperband supplied by Monarch is an engineered product for optimal performance in Reel Turn-Up Systems. Monarch offers a variety of unique packaging styles to best suit individual application and customer requirements. All paperband is produced from 100% Northern Virgin Softwood Fiber to ensure maximum strength and stiffness characteristics for highest turn-up success rates.

## Paperband Product Characteristics

Available colors	Types	Caliper	Width	Tensile Strength	Elongation	Repulpability
Brown / Natural (B)	Extra- Strength (ES)	0.049" / 1.25mm	0.747" / 19mm	350lbs	< 2%	>110 F
White / Bleached (W)	Extra-Density (XD)	0.049" / 1.25mm	0.747" / 19mm	335lbs	< 2%	>35 F
	Super-Markless (SM)	0.035" / 0.89mm	0.747" / 19mm	287lbs	< 2%	>110 F

## Individual Product SKUs & Naming Convention

### Standard Level-wound

SKU	Band Type	Color	Product Type	Band	Packing Information
2201BESP-1	2201 = Level Wound	B = Brown	ES = Extra-strength	P-1 = Paperband	+/- 1,750' / 533m per coil One coil per box 36 Boxes per pallets
2201WESP-1	2201 = Level Wound	W = White	ES = Extra-strength	P-1 = Paperband	

### Uniband

SKU	Band Type	Color	Product Type	Band	Packing Information
U2201BESP-1	U2201 = Uniband	B = Brown	ES = Extra-strength	P-1 = Paperband	600' / 183M per reel 7 reels per box 4,200' / 1'280M per box 20 Boxes – per pallet
U2201WESP-1	U2201 = Uniband	W = White	ES = Extra-strength	P-1 = Paperband	
U2201WXDP-1	U2201 = Uniband	W = White	XD = Extra-density	P-1 = Paperband	
U2201WSMP-1	U2201 = Uniband	W = White	SM = Super-markless	P-1 = Paperband	

Paperband must be stored in a dry place at room temperature.

Store in a cool, dry place between 68F and 75F (20C-24C) prior to use. Optimal storage conditions: 70F (21C) 50% relative humidity.